

CenturyArks Co., Ltd.

# SilkyEvCam<sup>\*</sup> powered by PROPHESEE

## Less Data and High Speed for Edge Computing



### Gen3.1(VGA) PROPHESEE Event Based Vision Sensor

- Independently & Asynchronously pixels, Sensing only contrast changes
- Event-Based Vision technology performance vs. Frame-based camera Generating 10x to 1000x less data
  - < 10mW(sensor) Enabling new levels of power efficiency \*< 2.5W camera total
  - > 10,000fps Achieving a higher equivalent temporal resolution
- Wide Dynamic Range (up to 120dB)
- METAVISION™ Intelligence\* : SDK of edge processing including AI.

\* support by PROPHESEE

#### Small Cube Event Based Camera with USB Type-C<sup>™</sup> interface

- Small size 30mm x 30mm x 36mm and light weight, easy to install anywhere.
- USB3.0 Type-C<sup>™</sup> interface, IX connector synchronous signal interface
- Turn Key Pack. Get data output after simple setup
  \*SilkyEvCam, USB Type-C<sup>™</sup> cable(1.2m), Lens, Mini tripod, Hardcase



SilkyEvCam Specifications			
Event Based Vision sensor	Model	PPS3MVCD (PROPHESEE)	
	Image size	Type 3/4 " (Diagonal 12mm)	
	Module effective pixels	VGA ( 640 (H) x 480 (V) )	
	Pixel size	15um x 15um	
	Typical Latency	200us	
Output	Interface (event data & control)	USB 3.0 (USB Type-C <sup>™</sup> connector)	
	Interface (Sync/Trigger)	IX Series Connector ( IX80G-B-10P : HIROSE ) (Plug: IX30G-B-10S-CV(7.0)   IX31G-B-10S-CV(7.0) )	
Camera	Power supply	USB Power (VBUS)	5.0 V
	Lens Mount type	C/CS Mount	
	Wide Dynamic Range	>120dB	
	Operating temperature	T operation	$0 \sim$ + 50 °C
	Storage temperature	T storage	- 30 $\sim$ + 80 $^\circ \!\!\! \mathbb{C}$
	Current consumption	500mA(max) , 200~300mA(Ave.)	
	Dimensions / Weight (w/o Lens)	30mm (W) x 30mm (H) x 36mm (D) / 40g	
	Accessories	USB3.0 Type-C <sup>™</sup> Cable 1.2m (w/ rock screw)	
Standard Lens	Model	M0814-MP2 (computar)	
	Focal length	8mm	
	F value	F1.4 – F16C	
	Angle of view	70deg	
	Focus range	100mm to infinity	
	Size / Weight	Ф33.5mm x 28.2mm / 62.6g	
Others	Turn Key Pack	Standard Lens / Mini tripod / Hardcase	
	SDK support by PROPHESEE	METAVISION™ Intelligence	

#### Solution example [High Speed Counting]





-USB Type-C<sup>™</sup> is a trademark of the USB Implementers Forum. -Product names mentioned here are registered trademarks of their respective owners. -Please note that certain information may have changed since the date of description.



3-13-1, Nishiazabu, Minato-ku, Tokyo, Japan, 106-0031 TEL. +81-3-6804-5752 ca\_sales@centuryarks.com Homepage: www.centuryarks.com PROPHESEE METAVISION FOR MACHINES